


RGB48/Nx G5 07W



Opaline Flex SB 50-7 RGB


Colour side bend LED line

Opaline Flex SB 50-78 RGB is a colour side bend LED line designed for outdoor lighting projects that need a creative and flexible lighting solution.


With a flexible polyurethane housing, the Opaline Flex SB 50-7 RGB can easily adjust to the geometry of building facades and structures while delivering a uniform light effect.

Fully encapsulated and protected from the elements, these high-quality LED lines are built for long-term professional applications.

DIMENSIONS



PHOTOMETRICS



SPECIFICATIONS

LIGHT TYPE	RGB
LEDs/M	48 LEDs/m
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 173 lm/m Light engine: 316 lm/m Red: 36 lm/m Green: 114 lm/m Blue: 24 lm/m
EFFICACY	Luminaire: 24 lm/W Light engine: 44 lm/W
LIFETIME	L90B10 60.000 h
CONTROL	Dimmable
VOLTAGE	24 VDC
WATTAGE	7.2 W/m 2.2 W/ft
CUTTING STEP	125 mm (4.92")
OTHER DETAILS	IP67 protection Bend radius: 15 cm (5.9")
DIMENSIONS	Width: 14 mm (0.55") Height: 16 mm (0.63") Max run: 9 m (30')
TEMPERATURE	Tc max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (13°F...122°F)