



IE RWE.EOP RGB96/Nx G5 011W



DIMENSIONS



PHOTOMETRICS



Opaline Flex Side

Colour side bend LED line

Opaline Flex SB 100-10 RGB is a colour side bend LED line designed for outdoor lighting projects that need a creative and flexible lighting solution.

With a flexible polyurethane housing, the Opaline Flex SB 100-10 RGB can easily adjust to the geometry of building facades and structures while delivering a uniform light effect.

Fully encapsulated and protected from the elements, these high-quality LED lines are built for long-term professional applications.

SPECIFICATIONS

LIGHT TYPE	RGB
LEDs/M	96 LEDs/m
COLOR CONSISTENCY	3-Step MacAdam
LUMINOUS FLUX	Luminaire: 263 Lm/m Light engine: 479 Lm/m Red: 57 Lm/m Green: 168 Lm/m Blue: 37 Lm/m
EFFICACY	Luminaire: 23 Lm/W Light engine: 42 Lm/W
LIFETIME	L90B10 60.000 h
CONTROL	Dimmable
VOLTAGE	24 VDC
WATTAGE	11.52 W/m
CUTTING STEP	62.5 mm (2.46")
OTHER DETAILS	IP67 protection Bend radius: 15 cm (5.9")
DIMENSIONS	Width: 14 mm (0.55") Height: 16 mm (0.63") Max run: 9.5 m (31')
TEMPERATURE	Tc max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (13°F...122°F)